



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : A61F 2/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/15141</p> <p>(43) International Publication Date: 23 March 2000 (23.03.00)</p>
<p>(21) International Application Number: PCT/US99/20929</p> <p>(22) International Filing Date: 10 September 1999 (10.09.99)</p> <p>(30) Priority Data: 98/11332 11 September 1998 (11.09.98) FR</p> <p>(71) Applicant (for all designated States except US): C.R. BARD, INC. [US/US]; 730 Central Avenue, Murray Hill, NJ 07974 (US).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): PAJOTIN, Philippe [FR/FR]; 26, rue du Maréchal Foch, F-49300 Cholet (FR).</p> <p>(74) Agents: HONEYMAN, Jason, M. et al.; Wolf, Greenfield & Sacks, P.C., 600 Atlantic Avenue, Boston, MA 02210 (US).</p>		<p>(81) Designated States: AU, CA, JP, MX, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published — <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: PREFORMED CURVED PROSTHESIS THAT IS ADAPTED TO THE EXTERNAL ILIAC VESSELS</p> <div data-bbox="503 1134 1120 1596"> </div> <p>(57) Abstract</p> <p>A prosthesis is provided for repairing a defect in a muscle or tissue wall. The prosthesis has a preformed shape that conforms to the wall to facilitate placement and minimize shifting of the prosthesis when positioned on the wall. The prosthesis may include a body formed of a sheet of surgical mesh fabric having a flexible body surrounded by a peripheral edge that may be welded or fused so that the body is capable of resuming the preformed shape after being temporarily deformed to allow for implantation. The body is adapted to the inclination of the external iliac vessels. In one embodiment, the body includes a first portion (1) configured with a shape of a cap and a second portion (6) with a substantially spherical shape that is connected to the first portion at a lower edge (2) thereof. The first portion has a first radius of curvature and the second portion has a second radius of curvature that is less than the first radius of curvature. The second portion (6) includes an outer edge (8) that forms an angle with the lower edge (2) of the first portion that is greater than 100° at the apex (4) of the prosthesis.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PREFORMED CURVED PROSTHESIS THAT IS ADAPTED TO
THE EXTERNAL ILIAC VESSELS

Background of the Invention

5 **1. Field of the Invention**

The present invention relates to an implantable prosthesis, and more particularly to a prosthesis for repairing a hernia.

10 **2. Description of the Related Art**

A defect in a muscle or tissue wall, such as a hernia, is commonly repaired with an implantable prosthesis that is configured to cover and/or fill the defect. In many instances, a flat sheet of an implantable, non-resorbable, flexible mesh material, such as BARD MESH, has been employed for the parietal repair of hernias and eventrations of the abdominal wall. However, a surgeon may experience some difficulty positioning the mesh between the parietal peritoneum and the abdominopelvic wall. The mesh may also fold or wrinkle and be difficult to maintain in position.

Applicant previously developed an implantable prosthesis for repairing a defect in a muscle or tissue wall to alleviate some of these concerns. The prosthesis, which is disclosed in WO 95/07666 and is assigned to C.R. Bard, the assignee of the present application, is made of an implantable, nonabsorbable and flexible material that is formed to independently assume a curved shape adapted to conform to the anatomical shape of the wall. The prosthesis includes a body comprised of a first portion formed in the shape of a cap and a second portion having a substantially spherical shape connected to a lower edge of the first portion. The second portion has a radius of curvature that is less than the radius of curvature of the first portion. The second portion includes an outer edge that meets the lower edge of the first portion at the apex of the body, which is the highest point of the curved prosthesis.

This prosthesis has proven useful and has become established in the practice of muscle or tissue wall repair in the inguino-femoral region. The prosthesis is not subject to stresses when deformed and, therefore, has no tendency to shift upon implantation. The prosthesis reinforces the abdominal wall at the anatomical region of concern.

It has nevertheless been observed that the reinforcement of the abdominal wall offered by the prosthesis could be extended.

It is an object of the present invention to provide an improved prosthesis for repairing a defect in a muscle or tissue wall by configuring the prosthesis with regard to certain anatomical zones.

5

Summary of the Invention

The present invention is an implantable prosthesis for repairing a defect in a muscle or tissue wall. The prosthesis includes a body of prosthetic material having a preformed three-dimensional contoured shape that independently assumes a curved shape adapted to conform to the wall. The body is configured to adapt to the inclination of the external iliac vessels to facilitate a desired placement of the prosthesis when employed for repairing an inguinal hernia.

According to one embodiment of the invention, the body includes a first portion with a first lower edge and a second portion with a second outer edge, the second portion being connected to the first portion at the first lower edge. The first portion is configured to have a shape of a cap and the second portion is configured with a substantially spherical shape. The first portion has a first radius of curvature and the second portion has a second radius of curvature that is less than the first radius of curvature. The second outer edge and the first lower edge meet at an apex of the body, the second outer edge forming an angle with the first lower edge that is greater than approximately 100° at the apex.

According to one aspect of the invention, the angle is between approximately 101° and approximately 120° .

According to another aspect of the invention, the first portion includes a first outer edge and the second portion includes a second outer edge, and the body further includes a third portion with a third lower edge and a fourth portion. The third portion is connected to the first outer edge and the fourth portion is connected to the third lower edge and to the second outer edge.

A depression may be formed between the second and fourth portions which is configured to be placed proximate the external iliac vessels when the prosthesis is positioned on a wall to repair an inguinal hernia. The angular orientation between the first lower edge and the second outer edge and the depression between the second and fourth portions are adapted to the inclination of the external iliac vessels to facilitate placement of and to minimize shifting of the prosthesis when positioned on the wall. The angular orientation and

the depression also provide a degree of deformation for matching adjacent contours.

According to a further aspect of the invention, the prosthesis is configured with a ratio of the surface area of the third portion to the total surface area of the prosthesis from approximately 0.25 to approximately 0.40.

5 According to still another aspect of the invention, the third portion has a third radius of curvature that is substantially equal to the first radius of curvature along the first outer edge. This configuration reduces the incidence of wrinkles or folds occurring between the first portion and the third portion so that the first and third portions do not partially cover each other upon or after implantation, thereby ensuring that the overall size of the prosthesis is
10 sufficient to adequately cover the desired portion of the wall.

Brief Description of the Drawings

The foregoing and other objects and advantages of the invention will be appreciated more fully from the following drawings, given solely by way of example, in which:

15 Figure 1 is a plan view of a prosthesis according to one illustrative embodiment of the invention;

Figure 2 is a cross-sectional view of the prosthesis taken along section line II-II in Figure 1; and

Figure 3 is a cross-sectional view of the prosthesis taken along section line III-III in
20 Figure 1.

Detailed Description

FIGS. 1-3 illustrate one embodiment of a prosthesis for repairing a defect in a muscle or tissue wall, such as a hernia. The prosthesis includes a body of prosthetic material that is
25 preformed with a three-dimensional configuration that conforms to the anatomical shape of the defective wall to facilitate placement and minimize shifting of the prosthesis when positioned on the wall. The body includes a plurality of shaped portions that are joined to each other to create a desired configuration. The particular orientation between several portions of the body is adapted to the inclination of the external iliac vessels to facilitate a
30 desired placement of the prosthesis when employed for repairing an inguinal hernia.

In one illustrative embodiment, the body includes first, second, third and fourth portions 1, 6, 10, 15, respectively, that are connected to each other to form a unitary structure.

Each of the portions includes a curved surface that provide the prosthesis with the preformed contoured shape.

The first portion 1 is formed with a substantially spherical shape and includes a first outer edge 2 and a first lower edge 3 joined to each other at an apex 4 of the prosthesis, which is the highest point thereof. The first portion 1 also includes a circular inner edge 5 that extends in the same plane as the outer and lower edges 2, 3.

The second portion 6 is disposed below the first portion 1 and includes an upper edge 7, a second outer edge 8 and a curved second lower edge 9. As shown, the upper edge 7 merges with the first lower edge 3 of the first portion.

The first and second portions 1, 6 are configured with an angle A at the apex 4 between the first lower edge 3 and the third outer edge 8 that positions the third outer edge 8 substantially opposite the external iliac vessels when implanted to repair an inguinal hernia. In one embodiment, the angle A is greater than 100° with an illustrative range of approximately 101° to 120° .

The third portion 10, which lies adjacent the first portion 1, includes a third lower edge 11 and a circular third outer edge 14. The third portion 10 is connected to the first portion 1 along the first outer edge 2.

The fourth portion 15 is positioned below the third portion 10 and adjacent the second portion 6. The fourth portion 15 is defined by and is connected to the third lower edge 11 of the third portion 10 and the second outer edge 8 of the second portion 6. The fourth portion also includes a curved fourth lower edge 16.

As illustrated in FIG. 1, the inner edge 5, the third outer edge 14 and the second and fourth lower edges 9, 16 form a generally D-shaped peripheral edge of the prosthesis. The peripheral edge may be welded or fused so that the body can regain its contoured shape after being deformed during implantation.

Each of the second and fourth portions 6, 15 may also have substantially spherical shapes to enhance conformance to a particular anatomical shape. In one illustrative embodiment, the radius of curvature of the second and fourth portions is less than the radius of curvature of the first portion to form surfaces in the second and fourth portions that have a steeper incline relative to the first portion.

The second and fourth portions are shaped to form a depression in the surface of the body that is configured to receive the external iliac vessels when the prosthesis is employed

for inguinal hernia repair. The depression extends inwardly from the peripheral edge between the second and fourth lower edges 9, 16 toward the apex 4.

The particular angular orientation between the first lower edge 3 and the second outer edge 8 and the depression between the second and fourth portions 6, 15 are adapted to the inclination of the external iliac vessels to facilitate placement of and to minimize shifting of the prosthesis when positioned on the wall. The angular orientation and the depression also provide a degree of deformation for matching adjacent contours.

The prosthesis may also be configured to substantially reduce the incidence of wrinkles or folds between the first and third portions so that the first and third portions do not partially cover each other upon or after implantation, thereby ensuring that the overall size of the prosthesis is sufficient to adequately cover the desired portion of the wall. In one illustrative embodiment, the first portion 1 has a first radius of curvature and the third portion 14 has a third radius of curvature that is substantially equal to the first radius of curvature along the first outer edge 2.

The prosthesis may be formed from an implantable, biologically compatible material that is nonabsorbable and flexible. In one embodiment, the prosthesis is formed of a knitted fabric of implantable polypropylene filament, such as BARD MESH, that includes a plurality of interstices (not shown) for promoting tissue ingrowth to the prosthesis. It is to be understood, however, that the prosthesis may be formed of any suitable material.

The prosthesis may be configured to have any shape and size suitable for a particular application. In one embodiment, the height H of the prosthesis from a plane defined by the peripheral edge and the apex 4 is approximately 21 mm. The first portion 1 has a substantially spherical shape with a radius of curvature of approximately 120 mm, particularly along the first outer edge 2. The third portion 10 has substantially the same radius of curvature of approximately 120 mm adjacent the first outer edge 2. The second and fourth portions 6, 15 each has a substantially spherical shape with a radius of curvature of approximately 35 mm. The total surface area of the prosthesis is approximately 44,780 mm², with the second portion 10 having a surface area of approximately 12,735 mm².

The disclosed configuration is particularly suited for repairing an inguinal hernia. It is to be appreciated, however, that this configuration is exemplary and that the prosthesis may be configured to have other shapes and sizes suitable for a particular application.

The preformed curved shape of the prosthesis may be obtained using any suitable manufacturing process. In one illustrative embodiment, the prosthesis is fabricated using a thermoforming procedure that includes placing a sheet of mesh fabric in a mold having the desired shape for the prosthesis, heating the fabric in the mold at an approximate temperature of 100°C to 200°C for a period of approximately 5 to 60 minutes, and subsequently cooling the fabric in the mold with an air flow having an approximate temperature of 15°C to 30°C for a period of approximately 5 to 60 minutes.

The edges of the prosthesis may be welded by fusing the meshes and the material using an ultrasonic welding procedure. During this procedure, the prosthesis is maintained between an element generating vibrations and an anvil that is configured to the particular dimensions of the prosthesis. In one embodiment, the edges are welded at a pressure of approximately 150 kPa to 800 kPa and an energy of approximately 100 to 5000 joules for a period of approximately 50 to 5000 milliseconds.

Once the sheet of mesh fabric has been shaped and the edges of the shaped prosthesis have been welded, any excess fabric extending beyond the welded edges is separated from the body of the prosthesis using a manual cutting procedure to form the completed prosthesis.

After inspection, the prosthesis may be packed in an internal packing (shell and insert) that has been designed specifically according to the three-dimensional characteristics of the prosthesis so as to comply with and protect the preformed curved shape of the prosthesis. The internal packing may be subsequently placed and packaged in a external packing for additional protection. The entire assembly may then be sterilized using any suitable method, such as with ethylene oxide, to provide a sterile prosthesis that is ready for implantation.

It should be understood that the foregoing description of the invention is intended merely to be illustrative thereof and that other embodiments, modifications, and equivalents of the invention are within the scope of the invention recited in the claims appended hereto.

What is claimed is:

Claims

1. An implantable prosthesis for repairing a defect in a muscle or tissue wall, the prosthesis comprising:

a body of prosthetic material having a preformed three-dimensional contoured shape that independently assumes a curved shape adapted to conform to the wall, the body including
5 a first portion (1) with a first lower edge (3) and a second portion (6) with a second outer edge (8), the second portion being connected to the first portion at the first lower edge (2), the first portion configured to have a shape of a cap and the second portion configured with a substantially spherical shape, the first portion having a first radius of curvature and the second
10 portion having a second radius of curvature that is less than the first radius of curvature, the second outer edge (8) and the first lower edge (3) meeting at an apex (4) of the body, the second outer edge (8) forming an angle with the first lower edge (3) that is greater than approximately 100° at the apex (4).

15 2. The prosthesis according to claim 1, wherein the angle is between approximately 101° and approximately 120°.

3. The prosthesis according to claim 1 or 2, wherein the first portion (1) includes a first outer edge (2) and the second portion (6) includes a second outer edge (8), and wherein
20 the body further includes a third portion (10) with a third lower edge (11) and a fourth portion (15), the third portion being connected to the first outer edge (2) and the fourth portion (15) being connected to the third lower edge (11) and to the second outer edge (8).

4. The prosthesis according to claim 3, wherein the third portion has a surface
25 area and the body has a total surface area, the prosthesis being configured with a ratio of the surface area of the third portion to the total surface area that ranges from approximately 0.25 to approximately 0.40.

5. The prosthesis according to claim 3 or 4, wherein the third portion (10) has a
30 third radius of curvature that is substantially equal to the first radius of curvature along the first outer edge (2).

- 8 -

6. The prosthesis according to claim 4, wherein the total surface area is greater than approximately 40,000 mm².

7. The prosthesis according to one of claims 3 to 6, wherein the fourth portion
5 (15) is configured with a substantially spherical shape.

8. The prosthesis according to one of claims 3 to 7, wherein the body includes a permanent depression between the second portion (6) and the fourth portion (15), the depression being constructed and arranged to be placed proximate the external iliac vessels
10 when the prosthesis is positioned on the wall to repair an inguinal hernia.

9. The prosthesis according to claim 8, wherein the body includes an apex (4), the depression extending inwardly from a peripheral edge of the body toward the apex.

15 10. The prosthesis according to one of claims 3 to 9, wherein the fourth portion (15) has a fourth radius of curvature that is substantially equal to the second radius of curvature.

11. The prosthesis according to one of claims 3 to 10, each of the second and
20 fourth portions (6, 15) includes a curved lower edge (9, 16).

12. The prosthesis according to any of the preceding claims, wherein the body includes a peripheral edge that is generally D-shaped.

25 13. The prosthesis according to any of the preceding claims, wherein the first radius of curvature is approximately 120mm.

14. The prosthesis according to any of the preceding claims, wherein the second radius of curvature is approximately 35mm.

30

15. The prosthesis according to any of the preceding claims, wherein the body of prosthetic material includes surgical mesh.

1/1




FIG. 2




FIG. 1




FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 99/20929

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61F2/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 836 838 A (COGENT) 22 April 1998 (1998-04-22) page 4, line 51 - line 55; claim 1; figures page 5, line 41 - line 50	1, 3, 5, 15
A	US 3 559 214 A (PANGMAN WILLIAM J) 2 February 1971 (1971-02-02) figures	1-3, 5, 12
A	WO 95 07666 A (BARD INC C R ; PAJOTIN PHILIPPE (FR)) 23 March 1995 (1995-03-23) cited in the application page 3, last paragraph - page 4, paragraph 2; figures 1, 2	1, 12, 15
A	US 5 584 884 A (PIGNATARO ANTHONY S) 17 December 1996 (1996-12-17)	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"B" document member of the same patent family

Date of the actual completion of the international search

13 December 1999

Date of mailing of the international search report

11/01/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Neumann, E

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/20929

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0836838 A	22-04-1998	FR 2754705 A JP 10179619 A	24-04-1998 07-07-1998
US 3559214 A	02-02-1971	NONE	
WO 9507666 A	23-03-1995	FR 2709947 A EP 0746267 A US 5954767 A	24-03-1995 11-12-1996 21-09-1999
US 5584884 A	17-12-1996	WO 9704722 A	13-02-1997